

HOGTUNES

Audio Solutions For The Great American Cruiser

Hogtunes Inc., Unit 14 - 70 Ellis Drive, Barrie, Ontario, Canada, L4N-8Z3

Tel: (705) - 719-6361 Email: info@hogtunes.com

www.hogtunes.com

2 Channel Side Plate (2CHSP) Installation Instructions



On the brake side of the bike, remove the 3 factory bolts shown by arrows (above), noting the brake side horizontal fairing support bracket will be removed, and not re-installed. Using the supplied fasteners, secure the amplifier to the plate so it is oriented in the same way as the picture above. Put the amplifier/plate assembly in place, and reinstall the 3 factory screws.

This kit includes a wire harness with a 4 pin blue plug, and a new main plug for your existing 2 channel amp. If you have your bike setup with a Hogtunes 4 Channel amp, and are adding a Hogtunes 2 channel amp to the system, the blue plug will plug into the “bypass out” plug on the 4 channel amp. This is what sends music from the 4 channel amp to the 2 channel amp. The white/black pair of wires on the 4 pin harness will plug into the green/black wires (brake side input) on the 2 channel amp. The red/black wires on the 4 pin harness will plug into yellow/black (clutch side input) on the 2 channel amp. The supplied harness for your 2 channel amp has 4 black wires that end in two 2 pin plugs which are “heat-shrunk” together. These wires send power from the 2 channel amp to the lowers. If you have any questions, please email tech@hogtunes.com or call 705-719-6361

Harley-Davidson, Electra Glide, Road Glide, Street Glide, Ultra Classic, and Tour-Pak are Trademarks, and/or Registered Trademarks of Harley-Davidson, Inc., Milwaukee, Wisconsin, USA, and if Used or Implied are for Reference Only.

There is No Affiliation Between Harley-Davidson, Inc., and Hogtunes Inc.