

HOGTUNES

Audio Solutions For The Great American Cruiser

Hogtunes Inc. Unit#14-70 Ellis Drive, Barrie, Ontario, Canada, L4N-8Z3

Tel: (705)-719-6361 Email: info@hogtunes.com

RG RM Grill Manual

For Use On Rushmore (2015+) Road Glides

Each factory grill will be removed from the inner fairing by prying up on them. Start with your fingers, but if you must use a tool, please use something with a 90° end being extra careful not to scratch your inner fairing, (especially if its painted)! On the back of each stock grill, you will see a rubber gasket and 2 white clips. These gaskets and clips will be removed from the factory grills and re-installed on the Hogtunes grills. Once the gaskets and clips are installed onto the new grills, simply press the new grills back onto your inner fairing.



NOTE: The factory clips must be removed carefully!

Using your thumbnails or a flat edge under each side, gently pry the 2 ends apart (as per the image) and pull up to release each clip from the stock grill. If you put a flat edge under one end only, the clip cannot release and you have a very good chance of breaking the clip.

On the back side of the grills, you will see tabs that are part of the metal mesh which are folded over to secure the mesh to the plastic trim ring. Folding these tabs back up allows the ring and mesh to separate easily for paint etc. The metal mesh is thick enough that it should not warp during such processes as powder coating, polishing, painting, chroming etc.