

# *Practice Safe Sound!*

Hogtunes speakers may play much louder than the OE, which can be a distraction to the rider and/or passenger. Please use caution when playing your stereo at high volume, especially in traffic.

You are a valued customer so please:

*Ride Alert*  
*Arrive Alive!*

## Technical Stuff

Power Handling: 45 RMS-90 Peak  
Frequency Response: 55-21K  
Sensitivity (#0902): 90 db 1watt/1meter  
Sensitivity (#1017): 89 db 1watt/1meter  
Nominal Impedance: 2 Ohms

*The Speakers in This Kit Are 2 Ohm and May Cause Damage If Used on OEM Radios Supplied Before Model Year 2006 .*

[www.hogtunes.com](http://www.hogtunes.com)

# **HOGTUNES**

*Audio Solutions For The Great American Cruiser*



Designed and Engineered in Canada

## **Installation Manual**

**For Model #'s 0902-AA/1017-AA**

*Direct Replacement Speakers For Touring Models With Advanced Audio Radios.*

*The Speakers in This Kit Are 2 Ohm and May Cause Damage If Used on OEM Radios Supplied Before Model Year 2006*

Rev 1.1

Congratulations and Thank-you for your purchase of Hogtunes speakers! Since positive word of mouth is the best way to grow our business, we want your new speakers to work as well as they were designed to. If you have any questions or concerns, we are here to help. Email [info@hogtunes.com](mailto:info@hogtunes.com), or call us during regular business hours (EST) at 705-719-6361. If you still need help, then please consider a professional installation by your motorcycle dealer.

**IMPORTANT:** The speakers in this kit are 2 ohm and designed for use with Advanced Audio radios or other devices that can play a 2 ohm load. Using this speaker on pre-2006 model year radios may cause damage to the unit.

## **# 0902-AA Fairing Installation Instructions**

**Step #1:** Remove the ground wire from the battery, or make sure your ignition switch stays in the “OFF” position.

**Step #2:** Remove your outer fairing/headlamp assembly, and set it aside. Refer to a service manual if you need help with this. With the outer fairing/headlamp assembly removed, locate the back of each speaker.

**Step #3:** Take the 2 wires off each speaker by gently pulling one at a time. Undo the screws that attach each speaker/grill assembly to the inner fairing and remove. Gently pull the stock speaker out of each grill assembly.

**Step #4:** “Clip” the Hogtunes speaker into each grill assembly. Position your new speaker/grill assembly onto the inner fairing, and re-attach each one using the OE screws. A hand screwdriver is recommended for this step.

**Step #5:** Hogtunes speakers are a direct replacement for the OE speakers. The female OE “in-line” connectors mate with the male connectors on each speaker, and only go on one way. If you are replacing aftermarket speakers, you may need to re-install the correct sized connectors (not supplied) onto the factory speaker wires.

**Step #6:** Once you are confident the factory wires are correctly attached to the new speakers, re-install the battery ground wire, and turn on your radio to confirm that both speakers are playing. Re-install your fairing/headlamp assembly. Your new speakers are ready to enjoy!

**Note:** Bass response will improve dramatically with the fairing on and all screws to factory torque specs.

## **#1017-AA Rear “Pod” Installation Instructions**

**Step #1:** Remove the ground wire from the battery, or make sure your ignition switch stays in the “OFF” position.

**Step #2:** Remove the factory speaker grills by undoing the 4 screws in each rear speaker “pod”. Carefully lift up on each speaker and take the 2 wires off by pulling one at a time from the stock speaker. Remove the speakers.

**Step #3:** Hogtunes speakers are a direct replacement for the OE speakers. The female OE “in-line” connectors mate with the male connectors on each speaker, and only go on one way. If you are replacing aftermarket speakers, you may need to re-install the correct sized connectors (not supplied) onto the factory speaker wires. Once you are confident the factory wires are correctly attached to the new speakers, sit them in place, put the grills back on, and secure the speaker by reinstalling the 4 screws per “pod”.

**Step#4:** Re-install the battery ground wire, turn your radio on and confirm that both speakers are playing. Your new speakers are ready to enjoy!

## **Warranty Information:**

Hogtunes speakers are warranted for a period of 20 years to the original purchaser. Proof of purchase is required for all warranty claims. **All Warranty claims must be made through the dealer this product was originally purchased from.** Products found to be defective during the warranty period will be replaced (with a product deemed to be equivalent) at Hogtunes sole discretion.

### **What Is Not Covered:**

- 1)Any expense related to the removal or re-installation of these speakers.
- 2)Repairs to these speakers performed by anyone other than Hogtunes.
- 3)Subsequent damage to any other components.
- 4)Any product purchased from a non-authorized Hogtunes dealer.
- 5)Damage to speakers from an accident or collision.

Here at Hogtunes, we design all products from the ground up, and specify all parts right down to the adhesives used to hold the speakers together. Since we are constantly testing and investigating different technologies, any and all specifications or features are subject to change without notice.